

Carbon Break™ has been specifically formulated to instantly dissolve all types of fire damage residues. Upon application, carbon, soot, grease and other organic soil will be suspended from surfaces for quick, easy removal.

DILUTIONS

Medium soil: 1 part with 15 parts of water.

Heavy soil: 1 part with 10 parts of water.

Carbon Break™

[water base soot remover & wall cleaner]



DIRECTIONS

- 1) Shake gently before use.
- 2) Always test for color stability before use.
- 3) Dilute according to soil conditions.
- 4) Apply solution to surface with a sponge, mop or low-pressure sprayer – avoid over-application onto other surfaces
- 5) Allow to dwell for 1 to 5 minutes, but do not let surface dry.
- 6) Rinse area well with clean water.

AVAILABLE SIZES

US gallon . 55-gallon drum

ADVANTAGES AND USAGES

- Excellent for use in the removal of soot, carbon, grease, heavy smoke residues and organic film.
- For use on walls, cabinets, property contents, floors and other hard surfaces.
- Leaves a pleasant fresh scent.
- User safe. Environmentally friendly.

TECHNICAL DATA

pH at use dilution	12.50
Compound type	nonionic
Water solubility.....	complete
DOT restrictions	none
Freeze/thaw stable	yes
VOC compliant	yes
Shelf-life, years	10+

CUSTOMER INFORMATION

Emulsifies and suspends hydrocarbons and other greasy soils resulting from fire damage.

Highly concentrated for extra savings.

Nontoxic. Biodegradable.



[fireplace soot]



[fire damage]



[smoke damage]